

1. The first step in the process is to identify the problem or issue that needs to be addressed. This involves gathering information and understanding the context of the problem.

(43) International Publication Date
10 March 2005 (10.03.2005)

PCT

(10) International Publication Number
WO 2005/021990 A2

(51) **International Patent Classification:** **F16D**

(21) **International Application Number:** **PCT/US2004/027964**

(22) **International Filing Date:** **27 August 2004 (27.08.2004)**

(25) **Filing Language:** **English**

(26) **Publication Language:** **English**

(30) **Priority Data:** **60/498,073 27 August 2003 (27.08.2003) US**

(71) **Applicant (for all designated States except US):** **BELL HELICOPTER TEXTRON INC. [US/US]; P.O. Box 482, Fort Worth, TX 76101 (US).**

(72) **Inventors; and**

(75) **Inventors/Applicants (for US only):** **STAMPS, Frank, B. [US/US]; 4705 Mill Crossing West, Colleyville, TX 76034 (US). SMITH, Michael, R. [US/US]; 1700 Tyler, Colleyville, TX 76034 (US). BOTHWELL, Christopher, M. [US/US]; 512 Coventry Drive, Grapevine, TX 76051 (US). CORSO, Lawrence, M. [US/US]; 9204 Glenhaven Court, North Richland Hills, TX 76180 (US).**


BRASWELL, James, L., Jr. [US/US]; 106 Williamsburg Court, Coleville, TX 76034 (US). **POPELKA, David, A.** [US/US]; 4705 Mill Brook, Coleville, TX 76034 (US). **SCHELLHASE, Ernst, C.** [US/US]; 8516 Mary Creek Drive, Fort Worth, TX 76116 (US). **HOLLIMON, Charles, L.** [US/US]; 6836 Megan Drive, North Richland Hills, TX 76180 (US). **NEWMAN, Thomas, J.** [US/US]; 175 E.P. Dawson Road, Maypearl, TX 76064 (US). **BASKIN, Bryan** [US/US]; 2804 Hedgeaway Drive, Arlington, TX 76016 (US). **CAMPBELL, Thomas, C.** [US/US]; 5448 Lake Powell Drive, Fort Worth, TX 76137 (US). **ROBERTSON, Daniel, B.** [US/US]; 1222 Ridgewood Circle, Southlake, TX 76092 (US).

(74) Agents: WALTON, James, E. et al.; Law Offices of James E. Walton, P.L.L.C., 1169 N. Burleson Blvd., Suite 107-328 Burleson, TX 76028 (US).

(81) **Designated States** (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,

[Continued on next page]

(54) Title: DUAL SPRING RATE DAMPER



(57) Abstract: A damper has a piston having an axis, an outer surface, and opposing ends. Elastomeric seals are in sealing contact with the outer surface of the piston, the seals being coaxial with the piston and limiting movement of the piston to a path along the axis of the piston. The seals also define fluid chambers adjacent the ends of the piston. A primary passage communicates the fluid chambers, and a selectively switchable valve for controls a flow of fluid from one of the chambers to another of the chambers through the primary passage. When the flow of fluid through the primary passage is permitted, movement of the piston is resisted by a first spring rate due to a shear force required to cause shear deflection of the seals. When the flow of fluid through the primary passage is restricted, movement of the piston is resisted by a second spring rate due to a fluid force required to cause bulging deflection of the seals.



PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished
upon receipt of that report

- (84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
10 March 2005 (10.03.2005)

PCT

(10) International Publication Number
WO 2005/021990 A3

(51) International Patent Classification⁷: **B60G 13/00**,
15/00, F16F 11/00, 7/00, 9/00, 5/00, 9/10, 9/34

76137 (US). **ROBERTSON, Daniel, B.** [US/US]; 1222
Ridgewood Circle, Southlake, TX 76092 (US).

(21) International Application Number:
PCT/US2004/027964

(74) Agents: **WALTON, James, E.** et al.; Law Offices of James
E. Walton, P.L.L.C., 1169 N. Burleson Blvd., Suite 107-
328, Burleson, TX 76028 (US).

(22) International Filing Date: 27 August 2004 (27.08.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60498,073 27 August 2003 (27.08.2003) US

(71) Applicant (for all designated States except US): **BELL
HELICOPTER TEXTRON INC.** [US/US]; P.O. Box
482, Fort Worth, TX 76101 (US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(72) Inventors; and

(75) Inventors/Applicants (for US only): **STAMPS, Frank,**
B. [US/US]; 4705 Mill Crossing West, Colleyville, TX
76034 (US). **SMITH, Michael, R.** [US/US]; 1700 Tyler,
Colleyville, TX 76034 (US). **BOTHWELL, Christo-**
pher, M. [US/US]; 512 Coventry Drive, Grapevine, TX
76051 (US). **CORSO, Lawrence, M.** [US/US]; 9204
Glenhaven Court, North Richland Hills, TX 76180 (US).
BRASWELL, James, L., Jr. [US/US]; 106 Williamsburg
Court, Colleyville, TX 76034 (US). **POPELKA, David,**
A. [US/US]; 4705 Mill Brook, Colleyville, TX 76034
(US). **SCHELLHASE, Ernst, C.** [US/US]; 8516 Marys
Creek Drive, Fort Worth, TX 76116 (US). **HOLLIMON,**
Charles, L. [US/US]; 6836 Megan Drive, North Rich-
land Hills, TX 76180 (US). **NEWMAN, Thomas, J.**
[US/US]; 175 E.P. Dawson Road, Maypearl, TX 76064
(US). **BASKIN, Bryan** [US/US]; 2804 Hedgeway Drive,
Arlington, TX 76016 (US). **CAMPBELL, Thomas,**
C. [US/US]; 5448 Lake Powell Drive, Fort Worth, TX

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

(88) Date of publication of the international search report:
12 May 2005

For two-letter codes and other abbreviations, refer to the "Guide-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: DUAL SPRING RATE DAMPER

(57) Abstract: A damper has a piston having an axis, an outer surface, and opposing ends. Elastomeric seals are in sealing contact with the outer surface of the piston, the seals being coaxial with the piston and limiting movement of the piston to a path along the axis of the piston. The seals also define fluid chambers adjacent the ends of the piston. A primary passage communicates the fluid chambers, and a selectively switchable valve for controls a flow of fluid from one of the chambers to another of the chambers through the primary passage. When the flow of fluid through the primary passage is permitted, movement of the piston is resisted by a first spring rate due to a shear force required to cause shear deflection of the seals. When the flow of fluid through the primary passage is restricted, movement of the piston is resisted by a second spring rate due to a fluid force required to cause bulging deflection of the seals.